




REBUILD REPAIR RECYCLE

Save up to
70%
less than a new unit



Before



After

12 Month
"Like New"
Warranty

Virtually all PHD products are field repairable, so your maintenance personnel can rebuild these products at your facility to save costs.

- Refurbish your existing PHD products with all new wear items.
- Get the same PHD quality that you're used to, but for minimal cost versus purchasing a new unit.
- Place your units back into service, and reduce your total cost, plus save valuable components from scrap.
- Receive a 12 month "like new" warranty on your rebuilt unit.

Replacement Parts

Distributor Assistance

Online Support

Fast In-House Rebuilds

All New Wear Items

Receive "Like New" Warranty

Contact your local PHD distributor today!



Contact your local PHD MDN Partner today or call PHD
phdinc.com/ned515
1-800-624-8511



phd
SOLUTIONS FOR INDUSTRIAL AUTOMATION
P.O. Box 9070 • Fort Wayne, IN 46899 USA

▲ Circle 30 on card or visit www.nedinfo.com/56396-30

SMOOTH MOVES

WITH CREFORM PLAICON ROLLER CONVEYORS.



Enhance roller conveyor flexibility. Creform® Plaicon® Roller Conveyors provide extra support and smooth flow for the difficult handling challenges of totes with soft bottoms, open cell designs or non-packaged parts. And, Plaicon has less vertical space requirements because precision rollers spin freely requiring less flow angle. Plaicon conveyors are quiet and easily combine with the Creform System of pipe & joints enhancing parts presentation ergonomics in manufacturing, kitting and order picking operations. *Make a smooth move and contact us today.*

CREFORM MATERIAL HANDLING SYSTEMS
www.creform.com • 800-839-8823



▲ Circle 31 on card or visit www.nedinfo.com/56396-31

UL-Listed Potting Compound

withstands high temperatures



Type 50-3150/RFR Black Epoxy with Catalyst 30 has a relative temperature index rating of 130°C, significantly higher than the 90°C RTI for most epoxies. This higher rating ensures that the potting compound will survive elevated temperatures for long periods of time.

Epoxies, Etc., Cranston, RI (800) 376-9437

▲ Circle 32 on card or visit www.nedinfo.com/56396-32

Pressure Sensor

comes in ranges from 750 to 30,000 psi



Model PX51-USBH pressure sensor with all stainless steel body, as well as choice of Imperial

or metric pressure ports, is a robust solution to get your pressure data directly to your computer. Transducer is temperature compensated from 60 to 160°F and can be operated between -50 and 185°F. Accuracy is ±0.25% FS, and span and zero thermal effects are 0.003% and 0.005% FSO/F, respectively.

Omega Engineering Inc., Stamford, CT (800) 826-6342

▲ Circle 33 on card or visit www.nedinfo.com/56396-33

Slim Refuse Container

styles meet variety of space needs



Slim Jim Step-On containers maximize space efficiency with a 20% smaller footprint and a slender profile ensuring a perfect fit in even the tightest spaces. Built-in dampener affords quiet and controlled lid closing. Slim Jim comes in five sizes and in front-step or end-step styles and in premium colors and finishes.

Rubbermaid Commercial Products, Huntersville, NC (540) 667-8700

▲ Circle 34 on card or visit www.nedinfo.com/56396-34

Custom Sheeter System

unwinds, cuts & stacks aluminum



This custom sheeter system with automated stacker will unwind, cut, and stack a 29-in. wide roll of 0.003-in. thick aluminum. Material is cut into 50-in. sheets and placed in 12-in. high stacks. PLC controls and

HMI color touch screen are provided for easy entering of operator information, including cut length, run time, and number of cut pieces.

AZCO Corp., Fairfield, NJ (973) 439-1428

▲ Circle 35 on card or visit www.nedinfo.com/56396-35